

HSF

NOTES:


Voltage Rating: 50V AC/DC
 Current Rating: 0.5AMP
 Contact Resistance: 20mΩ max
 Withstand Voltage: 500V AC/Minute
 Insulation Resistance: 500MΩ min
 Operation Temperature: -40°C to +105°C

Contact Material: Phosphor Bronze
 Contact Plating: 100~200u" Tin Plated Over
 50~80u" Nickel
 Insulator Material: PA9T+33%GF UL94V-0 BLACK

Ordering Information

3652- S XXX - 034 XX R03

No. of Pins	Plating	Packing
004: 04 Pin	G0=Gold Flash	R=Tape&Reel
005: 05 Pin	G3=10u"Gold	
006: 06 Pin	G4=15u"Gold	
007: 07 Pin	G5=30u"Gold	
008: 08 Pin	S0=Gold Flash/Tin	
010: 10 Pin	S3=10u"Gold/Tin	
017: 17 Pin	S4=15u"Gold/Tin	
020: 20 Pin	S5=30u"Gold/Tin	
	SN=Tin	



21.99	25.65	23.75	26.45	20
18.24	21.90	20.00	22.70	17
9.49	13.15	11.25	13.95	10
6.99	10.65	8.75	11.45	8
5.74	9.40	7.50	10.20	7
4.49	8.15	6.25	8.95	6
3.24	6.90	5.00	7.70	5
1.99	5.65	3.75	6.45	4
E	D	B	A	PIN数

				OPERATION	DRAW	DATE	SCALE	FIT	PART NO.
				X.X ±0.40	DingWenMin	2016.10.20	UNIT	mm	3652-SXXX-034XXR03
				X.XX ±0.25	CHECK	DATE	SIZE	A4	TITLE:
				X.XXX ±0.15	APPROVE	DATE	SHEET	1/1	1.25mm BTB FEMALE, 90° DIP, H=3.4, 不带柱
A0	2016.10.20	NEW		Angle ± 3'			PROJ.		Customer NO.
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	DIM TOL					

WCON
 Http: www.wcon.com

WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com	WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: salesks@wcon.com
---	--