

HSF

NOTES:



Rated Current:18.0 AMP
 Contact Resistance:8 mΩ Max
 Withstand Voltage:2000 V AC/DC
 Insulation Resistance:1000 MΩ min
 Operation Temperature:-40°C to +105°C
 Wire Range:30~12 AWG
 Wire Strip Length: 7 mm
 No.of Positions:2~20
 Screw Counter Torsion Force: 4.4 lbf.in Min.

Terminal Material:Phosphor Bronze
 Terminal Plating:Matte Tin Plated Over Nickel
 Pin Block Material:Brass
 Pin Block Plating:Nickel Plated Over All
 Screw Material: Steel
 Screw Plating:Nickel Plated Over All
 Up Cover Material:PA66 UL94 V-0
 Below Cover Material:PA66 UL94 V-0

Ordering Information:

P F 750 - A XX A SM W 1

F=Female Pitch 750=7.50
 No. of Pins 02-20P
 Color A=Green
 Contact Plated SM=Matte Tin
 Type W=With Screw



REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION		DRAW	DATE	SCALE	FIT	PART NO.
				X.X	±0.40					
				X.XX	±0.25	CHECK	DATE	UNIT	inch	TITLE:
				X.XXX	±0.15	APPROVE	DATE	SIZE	A4	7.50mm Pitch Female Pluggable Terminal Blocks
A0	2013/11/08	NEW		Angle	± 3'			SHEET	1/1	Customer NO.
				DIM	TOL			PROJ.		



WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com

WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: salesks@wcon.com