





# HSF

NOTES:  
 Rated Current:2.0AMP.  
 Contact Resistance:20mΩ Max.  
 Withstand Voltage:500V AC/DC  
 Insulation Resistance:1000MΩ Min.  
 Operation Temperature:-40°C to +105°C

Contact Material:Brass  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:PA9T+33%G.F UL94V-0 BK

Recommended P.C.B Layout (Top Side)  
 (PCB BOARD TOLERANCE±0.05)



## Ordering Information

1220-21 XX XX R XXX C 0 XX  $\Delta$

No. of Pins	Contact Plating	Pin Length	Insulator	Packing	Series No.
02~40	G0=Gold Flash G3=10u"Gold G4=15u"Gold G5=30u"Gold S0=Gold Flash/Tin S3=10u"Gold/Tin S4=15u"Gold/Tin S5=30u"Gold/Tin	L=A+B+D1+D2+4.2 Standard:	Material C=PA9T	0=PE Bag T=Tube	01~99

Item	Pin Length	A	D1	B	D2
Standard	---	2.80	---	2.80	---
Alternate					

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION	DRAW	DATE	SCALE	Fit	PART NO.
A1	2018/01/19	Modify P/N	$\Delta$	x.X ±0.40	Liu	2018.01.19	UNIT mm		1220-21XXXXRXXXC0XX $\Delta$
AO	2012/04/26	NEW	-----	x.XX ±0.25	CHECK	DATE	SIZE A4		TITLE: PH2.00 SINGLE ROW DOUBLE PLASTIC 90° H=2.0 MIDDLE BENDING
				x.XXX ±0.15	APPROVE	DATE	SHEET 1/1		Customer NO.
				Angle ± 3'			PROJ. $\phi$		
				DIM TOL					

**WCON**  
 Http: www.wcon.com

WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com	WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: salesks@wcon.com
---	--